



SOME SEE JUST A CABLE WESEE ONE SEE ONE WORLD ONE WORLD

CABLE LADDERS FOR BUILDINGS
 KS20

SURFACE TREATMENTS AND CORROSION CATEGORIES

Selection of the required surface treatment on the basis of the prevailing ambient conditions.

SURFACE TREATMENT OPTIONS				
Marking	Surface treatment	Corrosion category	Galvanization standa	rd
EG (EZ) Electro-galvanized after manufacturing	Galvanized steel. Coating thickness 5-8 µm	C1, C2	EN ISO 2081	Electro-galvanizing refers to covering the product with a layer of zinc, using electricity. Electroplating is made in an electrolyte bath, after several cleaning and treatment stages.
PG Pre-galvanized steel	Galvanized steel. Coating thickness approximately 20 µm	C1, C2	EN 10346	Pre-galvanized steel products are made of zinc-coat- ed steel bands. These products are also referred to as sendzimir galvanized products.
HDG Hot-dip galvanized after manufacturing	Galvanized steel. Coating thickness approximately 55 µm	C3, C4	EN ISO 1461	Hot-dip galvanized products are made of steel and finished product, such as a whole cable ladder or a part of it, is pre-treated and dipped in molten zinc. These are also referred to as hot-dip zinc coated products. The zinc coating covers the entire product, including cutting edges and weld seams.
SS316 Acid-proof stainless steel, AISI 316L	Acid-proof steel AISI 316L	C4, C5	-	Products made of acid-proof stainless steel are used in highly corrosive environments, where hot-dip gal- vanizing does not provide sufficient corrosion pro- tection.
M Painted steel	Painted steel. Standard colour white RAL 9010	C1, C2	-	Paint-coated steel products are made of pre-gal- vanized, painted steel band. The surface is covered with polyester paint, which has high resistance against weather, corrosion, and wear.
PURAL Painted steel	Pural coated steel Standard colour grey RAL 7045	C3, C4	-	Chemical consistency of Pural coating is optimized to tolerate weather conditions. Pural coating has igh resistance against corrosion and UV radiotaion.

CORROSION CATEGORY					
Corrosion category	Usage outdoors	Usage indoors	Required surface treatment	Thickness reduction	
C1 Very low	Not for outdoor use.	Heated buildings with a clean at- mosphere, such as offices, schools and hotels.	EG (EZ), PG, M	0,0 μm - 0,1 μm in a year	
C2 Low	Atmospheres with low contamina- tion levels. Mostly rural areas.	Unheated buildings with possible condensation, such as warehouses and sports halls.	EG (EZ), PG, M	0,1 µm - 0,7 µm in a year	
C3 Medium	Urban and industrial atmosphere with medium sulphur dioxide levels. Coastal areas with low salinity levels.	Production premises with high humid- ity levels and some impurities in the air, such as food industry facilities.	HDG, PURAL	0,7 μm - 2,1 μm in a year	
C4 High	Industrial areas and coastal areas with medium salinity levels.	Chemical industry production plants, coastal shipyards and boatyards.	HDG, PURAL	2,1 μm - 4,2 μm in a year	
C5-I, C5-M Very high (industrial)	Industrial areas with high humidity levels and a corrosive atmosphere. Coastal and other areas with high salinity levels.	Buildings or areas with almost constant condensation and high contamination levels.	55316	4,2 µm - 8,4 µm in a year	

RECOMMENDED PRODUCTS			
C1 - C2	C3 - C4	C5-I, C5-M	
 Pre-galvanized PG and electro-galvanized EG products Cable ladders Cable trays Wire mesh trays Lighting tracks 	 Hot-dip zinc coated HDG and Pural painted products Cable ladders Wire mesh trays Lighting tracks 	 Acid-proof SS316 products Cable ladders Wire mesh trays Lighting tracks 	

EARTHING AND EQUIPOTENTIAL BONDING

Main equipotential bonding must be carried out in each building. The purpose of main equipotential bonding is to prevent the occurrence of dangerous voltage differences between conductive parts that may be touched at the same time.

In equipotential bonding, exposed conductive parts and other conductive parts are connected to the same potential, to eliminate potential differences between them.

Parts connected to the main equipotential bonding usually include the building's metal pipelines (HVAC), metal constructions, and, where applicable, the main reinforcing steels used in concrete constructions.

Metal cable support systems can also be regarded as structures to be included in the equipotential bonding.

Protective earthing/equipotential bonding

Cable ladders, cable trays and lighting tracks can be regarded as exposed conductive parts, which means that they must be connected to the building's main equipotential bonding rail at least at one point.

In industrial installations in particular, special attention must be paid to the earthing and reliability of the entire cable ladder system.

In industrial applications, it is recommended that the cable ladder be connected to earth at an interval of 40 m, for example, unless it is reliably connected to a conductive structure (e.g. an earthed steel column).

Extension piece SSR, which is used with cable ladder types KS20 and KS80, provides sufficient electrical connection, so a separate grounding conductor need not be installed across the ladder extension.

Electrical conductivity (cable ladders)			
Product	Impedance mΩ/m		
K520 PG	0,60		
K580 HDG	0,44		
K580 55316	2,48		
KSF80 HDG	0,44		
Product + extension	Impedance mΩ/m		
KS20-300 PG + NL PG	0,24		
K520-300 PG + SSR PG	0,13		
K520-300 PG + SSC PG	0,24		
K580-300 HDG + NL HDG	0,39		
K580-300 HDG + NL-TK HDG	0,26		
K580-300 HDG + SSR HDG	0,17		
K580-300 HDG + SSU HDG	0,14		
SS316 KS80 + SS316 SSU	0,66		
KSF80-300 HDG + M10 pultit	0,16		
KSF80-300 HDG + KSF-NL HDG	0,30		
Measured at 50 mm from the extension.			





				Ceiling su	upport TP1
		-		Code	Product
	~	-		1449603	TP1-750 HDG
	r			1449604	TP1-1000 HDG
				1449606	TP1-1500 HDG
				Gate sup	port TPK
_				Code	Product
				1449492	TPK-200 HDG
				1449493	TPK-300 HDG
\sim				1449494	TPK-400 HDG
				1449495	TPK-500 HDG
				1449496	TPK-600 HDG
\leq		H.			
- 8		~		>	-
	r i				
acket KK	-мк				
ie P	roduct				_
49249 K	K-MK PG		T-branch	bracket VF	:
			Code	Product	
		/	1449890	VF PG	
				7	
	Wall sup	port V	к		
	1449591	VK-20	2KN HDG	1	
	1449592	VK-30) 2KN HDG	1	
	1449593	VK-40	2KN HDG	1	
				_	

1449594 VK-500 2KN HDG 1449595 VK-600 2KN HDG





Scankab set out as the cable ind**ust**ry's answer to "gar<u>age rock"</u>

From the outset in 1992, Scankab was the rebel of the cable industry. The business sold cables from a small garage store room and challenged the cable market. Most recently, Scankab has made its mark as a front runner in

fireproof cables (CPR).

Scankab develops, manufactures and supplies quality cables and cable management to electrical contractors, industry, marine & offshore, infrastructure and energy. The range includes more than 3,500 types of cables held in stock. Scankabs headquarter is based i Denmark in the western part of Funen and there are subsidiaries in Norway and Sweden.



We believe in direct communication

Denmark Phone +45 6343 1545 www.scankabsystems.dk **Noray** Phone +47 416 32 619 www.scankabsystems.no **Sweden** Phone +46 730-344 606 www.scankabsystems.se Solo